

Section _____ Town _____ Range _____

1906
18

I commenced a Survey of Section 19, T. 7, R. 7
for *Thomas J. Swaby et al*

C. B.

Dep. T. M. Parker
by L. F. Parker Surveyor Greene County.

Var.

Course.	Point of Beginning.	Chains Distance.	Corrected Bearings.
W	cent $\frac{1}{4}$	35.65	N 81° 0'
N	SW	40.02	" 8°
E	SW	35.89	" 3° 10'
N	S -	39.96	" N 81° 0'
S	N $\frac{1}{4}$ SW	39.97	
E	cent $\frac{1}{4}$ SW	19.45	
E	SW	63 rods	to corner stone of Morris Chapel Church. Hickory dia 12 N 35° E 88 lbs

CORNER ESTABLISHED.	Monument.	Device.	WITNESS POINTS OR BEARING TREES.	Mark or Dia. in Inches.	COURSE.	Links Distant.	REMARKS.
W $\frac{1}{4}$ SW	stone	+	Bl walnut	3	N 13° E	183	
S $\frac{1}{4}$ SW	stone	+	water oak	5	N 88° E	148	
E $\frac{1}{4}$ SW	stone	+	" oak	6	S 47 $\frac{1}{2}$ E	269	
cen SW	stone	+					